



1

UNATS

.XIIII

121 380 4600

e.org.uk

44 (0) 121 333 4109

www.hae.org.uk

stand, which raises the height of the mixer

1. Your Belle minimix is supplied with a

take care not to damage the threads.

8. Reverse this procedure to refit the drum,

unscrewed, lift the drum off carefully.

transportation, switch of, stand in front of the mixer and turn the drum anticlockwise. When it has fully anticlockwise.

7. To remove the drum for storage or

6. Always store the mixer in its normal

removing any stubborn residue of the

the rotating drum will greatly assist

shovels full of clean gravel, with water, in

the drum and the mixer is washed clean

5. When you have finished work, make sure

4. Ensure the drum is rotating while

3. The rotation of the drum is slow but very

other than the mix into the drum while it

a full load would be difficult and would

loading. Do not load a concrete mix into a stationary drum. Starting the mixer with

Always start the drum rotating before

2. Do not put your hand, shovel or anything

powerful. It will not stop rotating until the engine is stopped. Keep your hands out

before the cement mix hardens.

.nonisod inginqu

emptying the mix.

strain the drum shatt.

or the way.

rotating.

٠.

Betore Starting Work.

Useful Reference Points • www.hae.org.uk/businessguard

พกษอ

It is important to read this entire leaflet

BEFORE using the Belle Minimix Cement Mixer

1. Plan your work and think ahead to make sure you will always be

2. Petrol is highly flammable. Take care not to cause a fire or

Cement mixes are harmful to eyes, lungs and skin. Follow any instructions given by the manufacturers of these cement

working safely.

explosion.

products

vyse.org.u

ail@hae.org.uk

44 (0) 121 333 4109

before you start the cement mixer, you

rotate and will not stop rotating until the

When you start the engine the drum will

Check that the mixer is sited firmly and

not use the mixer - contact the hire

stand. If anything is found damaged, do

also need to wear appropriate personal

tull trousers to prevent the mixes coming You should wear gloves, long sleeves and

You must wear safety boots (EU345 or

FFP3(s) protection) when you are mixing

67 LNJ to muminim a minimum of EN149

BS2035) when you are working with this

You must wear goggles (EN166 or

may require a higher level of protection.

mixer. Particular jobs or environments

3. You will need to wear an appropriate

6. Anybody who is working near to you will

J. Check your machine, engine, drum and

BELLE MINIMIX CEMENT MIXER

into contact with your bare skin.

materials that cause dust.

brotective equipment.

.(2764/078128).

machine.

. Make sure you understand the controls

must know how to stop it.

safely near to your work area.

eudiue is stopped.

company.

3

.s

'G

°t

Belle Minimix Cement Mixer

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

Using the Belle Minimix Cement Mixer

STARTING THE ENGINE

- Check that the engine and machine controls are set correctly. 1.
- 2. Make sure that you hold the machine firmly so it will not move when you pull the starter.
- 3. Pull the starter handle slowly until you can feel that the starter has engaged with the engine, then pull it quickly and strongly. Don't pull it too far, or it may break
- Guide the cord back into place so that it recoils correctly. 4.

USING THE BELLE MINIMIX CEMENT MIXER

- Wear your protective equipment including ear defenders, dust mask, goggles and safety 1.
- 2. The engine must be running all the time there is a mix in the drum.

Hire Association Euro

2450 Regents Court

lihull B37 7YE

The C

move your fuel can to a safe, cool place.

10. Put all fuel caps back on properly, and

9. If you spill any fuel on your clothes,

8. If you spill any fuel on the ground, wipe it

7. Wipe any fuel off the machine. Dispose of

6. Do not fill the tank too full, this will help

brevent petrol seepage when you tilt the

Use a funnel and clean petrol when

Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.

drum; the petrol and oil may seep to other parts of the machine.

heavy or if the ground is rugged, use two

sited. If you teel the mixer/stand is too

the upright position. Make sure it is firmly

the clip. Thit the stand and mixer back into

Locate the stands on the opening of the drum. Locate the stand into position and lock

Alternatively one man can tip the mixer so

mixer onto the stand and secure with the

The stand should be sited on firm level

to make it easy to empty the drum into a wheelbarrow. The mixer can be used with

3. Two persons can then lift and locate the

ground near to your work area.

or without the stand.

5. Do not leave the mixer standing on the

3. If possible move the machine away from

2. Stop the engine and let it cool down.

Do not spill any fuel on

change them straight away.

tuel soaked cloth caretully.

yourself or the machine.

up or cover it with soil.

mixer.

.enelling.

и Ио ѕтокілд.

BEFUELLING

.aidoad

. Скира Справи

your work area.

'G

·t

°t

.S.

OWI

- 3. Do not move the mixer while the drum is full.
- 4. Stop the engine if leaving the machine unattended
- You must clean the mixer and especially the drum as soon as you have finished work, 5. before the mix goes hard.
- If your equipment does not work properly do not attempt to repair it. Contact the hire 6. company

Please keep this leaflet safely as it may be required for future reference

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

- 4. This Belle minimix cement mixer is designed for mixing concrete, mortar, plaster and similar compounds with water. IT can also mix composts and other similar materials.
- The action of this mixer can cause injury or damage if the machine is not used in a careful 5. and controlled way.
- 6. If you have not used a Belle mini mix cement mixer before, familiarise yourself with how the machine works before you start on the main task.
- You must have at least the following items of personal protective equipment: goggles: EN166 or BS2092; dust mask - a minimum of EN149 FFP3(s) protection; safety boots to EN345 or BS1870/4972; gloves.
- 8. This machine must not be used by minors, or by anyone under the influence of drugs or alcohol.
- 9. This Belle mini mix cement mixer is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



effort has been made by HAE/EHA to ensure that the information given in this docun is accurate and not misleading. HAE/ETA cannot accept responsibility for any lo to have arisen from the use of any such document/material. Only Acts of Parliament . bility p ent and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

:lism3



3YT TEB Iludilos The Crescent Birmingham Business Park มกอา รมมอติอม กระว

extractior

Thoroughly



suonia de wolu whenever you use this equipment (ppe) are the minimum that 1. The following items of personal protective

SROTARAGO

- barriers around your work area.
- Φ. Protect other people from the noise and dust, warn others to keep away, put

and that no-one is near to you or could

ventilation will almost always be required.

Mechanical

the ventilation required has been fully

other indoor situations it its suitability and

in domestic premises and only use it in

carbon monoxide poisoning. Never use it

confined spaces could cause fatal

Using this equipment indoors or in

tumes from petrol, or gas cylinders.

Do not use this cement mixer where there is a danger of explosion. It will ignite threas from partial or case eviladore

no further contact. If the rash persists

Mild dermatitis will heal providing there is

advice if you get any type of cement mix

off your skin immediately. Thoroughly rinse out your eyes and seek medical

rash occurs only where the substance

usually itchy and causes flaky skin. The

occrit when the skin reacts to certa

2. Contact dermatitis is a rash that may

7. Wet cement mix is a substance that can

CEMENT MIXES AND CONTACT

The rash can vary but it is

3. Wash cement or plastic or plaster mixes

was in contact with the skin.

cause contact dermatitis.

passasse

WORK AREA

.men ni

substances.

SITITAMRAD

seek medical advice.

·7

- not logilar

3. Make sure that the area is clear and safe