Useful Reference Points • www.hae.org.uk/businessguard

Betore Starting Work.

AAHA XHOW

- ignite fumes from petrol or gas there is a danger of explosion. It will Do not use this brush cutter where
- never run the brush cutter indoors or injury from breathing toxic tumes, To reduce the risk of serious or fatal .S cylinders.
- Make sure that the area is clear and 31 in poorly ventilated locations.
- or could distract you. sate and that no-one is near to you
- and form injury. Keep people at least Protect other people form the noise ·t
- ·'G 10 metres (32 feet) away.
- other debris that could foul your stones, wire, stout branches and Before starting, clear the area of

sepera buind

- minimum that should be worn brotective equipment (ppe) are the 1. The following items of personal **SROTAR340**
- You must wear a faceshield (EN166 -.S require a higher level of protection. Particular jobs or environments may whenever you use this brush cutter.
- other debris from where you are brush cutter may throw up stones or working with this machine. The B or BS2092 grade 1) when you are
- noise levels up to 102 dB(A) wear .guixrow
- hearing protection for this level as a appropriate ear muffs or plugs giving
- 3. This equipment is likely to cause

......

3YT TEB Iludilos The Crescent Birmingham Business Park :lism3 nuou sinegen uce :euoudeie Association Europe

'G

·+

31

.S

-7

.9

. G

**

1643 Safety Guidance

Brush Cutter

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

The sharp blades on the cutting head rotate very fast and can cause injury or

If you have not used a brush cutter before, familiarise yourself with how the

You must have at least the following items of personal protective equipment:

faceshield - impact resistant EN 166-B or BS2092 grade 1; ear muffs or plugs

giving protection for levels up to 102 dB(A); safety helmet to EN397 or BS5240;

This machine must not be used by minors, o by anyone under the influence of

This machine is designed for operation by an able bodied adult. Anyone with

either temporary or permanent disability must seek expert advice before using it.

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia

is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perc nave arisen from the use of any such document/material. Only Acts of Parliament and Statutory Ins

to have arisen from the use of any such document/material. Only Acts of Parliament and Statu have the force of law and only the courts can authoritatively interpret the law.

v:122016

4 STROKE PETROL

It is important to read all of this leaflet

BEFORE using the Brush Cutter

1. Plan your work and think ahead to make sure you will

Petrol is highly flammable. Take care not to cause a fire

This brush cutter is designed for cutting brush,

damage if the machine is not used in a careful and controlled way.

undergrowth, grass and small irate attachments.

machine works before you start on the main task.

safety bots to EN345 or BS1870/4972; gloves.

always be working safely.

or explosion.

drugs or alcohol.

2.

3.

5.

6.

7.

8

w.hae.org.ul

ail@hae.org.uk

44 (0) 121 333 4109

company for the material being cut.

of blades recommended by the hire

Make sure you use the correct type

covered during storage or transport,

The cutting blades should be

Brushcutters should only be used at

Do not operate this brush cutter

Do not use anything found damaged

equipment including the harness.

will also need to wear appropriate

Anybody who is working near to you

when changing or adjusting the

You should wear gloves especially

You must wear safety boots (EN345

prevent it getting caught up in the

machine. Tie up any long hair to

(BS5240) when working with this

You must wear a safety helmet

1. Check your machine, engine and all

personal protective equipment.

to protect the blades and you.

or near ground level.

BRUSH CUTTER

or BS1870/4972).

.sepsia

machine.

without using the harness.

contact the hire company.



- 9

·.

3

.S.

-2

- change them straight away. 7. If you spill any fuel on your clothes, caretully.

- 8. Put all tuel caps back on properly

Dispose of fuel soaked cloth

Wipe any fuel off the machine.

refueling. Do not spill any fuel on

around it to prevent dirt falling into

Clean the filler cap and the area

It possible, move the machine away

Stop the engine and let it cool down.

prush cutter, you must know how to

the controls. Before you start the

cutting blades is in place and

9. Make sure that you understand all of

8. Make sure the guard around the

correct manner. Do not improvise.

attachments and fit them in the

Only fit the correct cutting

adjusting the blades or the guard.

6. Wear your gloves when fitting or

5. Use a funnel and clean petrol when

yourseit or the machine.

from your work area.

sdjusted correctly.

the fuel tank.

·биіхошя ом ·г

BEFUELLING

.ti qota

44 (0) 121 380 4600

44 (0) 121 333 4109

ae.org.u e.org.uk

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

For guidance on managing

construction health risks go to www.hse.gov.uk/construction

Using the Brush Cutter

1. Wear your protective equipment including ear defenders, helmet, faceshield and

Always hold the brush cutter with both hands as well as using the harness.

Beware of debris and dirt that may be thrown up by the blades.

Make sure the cutting head is running at full speed before starting to cut into the

If the brush cutter starts to labour and slow down do not force it so hard. Do not

10. If you need to make adjustments to the blades or guard, stop the engine and wait

12. If your equipment does not work properly do not attempt to repair it. Contact the

Please keep this leaflet safely as it may be required for future reference

until the blades have completely stopped. Wear your gloves to prevent cutting

Attach the brush cutter to your harness carefully.

Make sure there is no-one in your area of work.

Keep the cutting head at or near ground level.

Stop the engine if someone approaches you.

your hands while you make the adjustments.

11. Stop the engine before leaving the machine unattended.

Hire Association Europe

2450 Regents Court

part througe setting.

is running smoothly.

that it recoils correctly.

far or it may break.

sny obstruction.

PION COID

piace.

hire company.

cold start without using the choke or

use it. Return the brush cutter to the

while the machine is idling, do not

squeeze and release the throttle to

Guide the cord back into place so

quickly and strongly. Don't pull it too

engaged with the engine, then pull it

you can teel that the starter has

prevent movement, you will damage

Do not put your foot on the rube to

not move when you pull the starter.

with the cutting attachment clear of

The choke should be pulled put and

and move your fuel can to safe, cool

3. Hold the brush cutter firmly so it will

2. Lay the brush cutter on the ground

1. Set the engine controls correctly.

STARTING THE BRUSH CUTTER

the part throttle lock engaged.

4. Pull the starter grip out slowly until

8. If the cutting attachment rotates

Y. Turn the choke off when the engine

6. As soon as the engine has fired,

release the part throttle setting.

1. Follow the same procedures as for a

safety boots.

brush.

overload the engine.

hire company.

2.

3.

4

5.

6.

7.

8.

9.

©Copyright Hire Association Europe April 2011

The Crescent oham Business Park olihull B37 7YE

тон пэлW

<u>9</u>